

Common Products Electronic parameter Specification

	5KΩ	10KΩ	10KΩ	10KΩ	10K Ω	50K Ω	100K Ω	100K	100K Ω
B_{25/50}	3270	3380	3470	3600	3950	3950	4000	4100	4300
B_{25/85}	3320	3435	3530	3630	3990	3990	4050	4160	4410
-30°C	52.84	111.3	127.5	133.6250	181.7	908.3	1790	1686.	2056.7
-25°C	41.19	86.39	97.10	101.6000	133.5	667.6	1321	1260	1502.2
-20°C	32.44	67.74	74.80	77.9250	98.99	494.4	984.7	954.7	1107.0
-15°C	25.65	53.39	58.08	60.2925	74.06	370.3	740.8	726.0	822.68
-10°C	20.48	42.45	45.44	47.0150	56.06	280.3	562.3	555.1	616.42
-5°C	16.43	33.89	35.82	36.9450	42.81	214.1	430.5	430.7	465.45
0°C	13.29	27.28	28.46	29.2350	32.96	164.8	332.3	337.2	352.4
5°C	10.80	22.05	22.78	23.3050	25.57	127.9	257.5	259.4	270.0
10°C	8.839	17.96	18.36	18.6850	20.00	99.98	201.1	203.3	208.3
15°C	7.266	14.68	14.90	15.0875	15.76	78.79	158.2	160.5	161.9
20°C	6.013	12.09	12.17	12.2450	12.51	62.55	125.4	120.7	126.7
25°C	5.000	10.00	10.00	10.0000	10.00	50.00	100.0	100.0	100.0
30°C	4.179	8.313	8.264	7.9340	8.048	40.24	80.29	79.6	78.35
35°C	3.508	6.941	6.890	6.7738	6.517	32.58	64.87	63.02	62.37
40°C	2.962	5.828	5.738	5.6230	5.321	26.56	57.72	51.39	49.94
45°C	2.510	4.912	4.810	4.6913	4.356	21.78	43.10	42.06	40.22
50°C	2.138	4.161	4.064	3.9265	3.588	17.94	35.42	34.51	32.56
55°C	1.826	3.537	3.448	3.3043	2.972	14.86	29.26	28.06	26.40
60°C	1.568	3.021	2.934	2.7928	2.467	12.38	24.30	23.16	21.53
65°C	1.351	2.589	2.504	2.3726	2.073	10.36	20.27	19.38	17.69
70°C	1.169	2.229	2.146	2.0210	1.734	8.717	16.99	15.93	14.62
75°C	1.014	1.924	1.845	1.7288	1.473	7.364	14.31	13.37	12.10
80°C	0.8838	1.669	1.592	1.4858	1.250	6.248	12.10	11.14	10.05
85°C	0.7725	1.451	1.378	1.2818	1.065	5.324	10.27	9.371	8.376
90°C	0.6774	1.226	1.195	1.1088	0.911	4.555	8.758	7.891	7.004
95°C	0.5963	1.108	1.039	0.9640	0.7824	3.912	7.459	6.687	5.894
100°C	0.5267	0.9735	0.966	0.8377	0.6744	3.372	6.438	5.699	4.978
105°C	0.4656	0.8574	0.7949	0.7344	0.5834	2.917	5.550	4.875	4.215
110°C	0.4130	0.7579	0.7028	0.6429	0.5066	2.533	4.801	4.195	3.580