

Common Products Electronic Parameter Specification

Part No.	R _{25°C} (KΩ)	B(K) 25/50°C	Rated Power @25°C (mW)	Dissipation Factor(δ) (mW/°C)	Thermal Time Constant (S)
TS502□3274A	5.0	3274 ±1%	10-20	2-4	5-20
TS502□3435B	5.0	3435 ±1%			
TS502□3470A	5.0	3470 ±1%			
TS502□3950A	5.0	3950 ±1%			
TS103□3274A	10.0	3274 ±1%			
TS103□3435B	10.0	3435 ±1%			
TS103□3470A	10.0	3470 ±1%			
TS103□3950A	10.0	3950 ±1%			
TS103□4100A	10.0	4100 ±1%			
TS153□3950A	15.0	3950 ±1%			
TS153□4100A	15.0	4100 ±1%			
TS203□3950A	20.0	3950 ±1%			
TS203□4100A	20.0	4100 ±1%			
TS223□4200A	22.0	4200 ±1%			
TS403□3928A	40.27	3928 ±1%			
TS503□3950A	50.0	3950 ±1%			
TS503□4100A	50.0	4100 ±1%			
TS104□3950A	100	3950 ±1%			
TS104□4100A	100	4100 ±1%			
TS104□4400A	100	4400 ±1%			

◆Special part number could be custom designed.